Vacc-Safe

ULT Freezer

VS-86L568 568 Litre

Suitable for storing **vaccines**, **medicines** and **laboratory products and samples** between -40°C and -86°C in pharmacies, hospitals, medical clinics and laboratories.





VIP Plus Insulation.

Provides up to 30% more storage capacity than a conventionally insulated freezer.



Increased Product Lifespan.

Dissipates heat 20% more effectively to improve life expectancy of core parts.



Multi-layer Silicone Sealing Structure.

Provides a tight seal between inner and outer door for better insulation.



Heated Pressure Equalization Port.

Allows users to re-open the main door quickly.



Improved Cooling Performance.

Patented Smart-Inverter technology significantly reduces the amount of energy consumed whilst maintaining superior temperature stability.



Built-In Backup Battery



Security



Single LED Display



USB Data



Lockable

Vacc-Safe

ULT Freezer VS-86L568 568 Litre



885 mm

Product structure data	
Temperature Range	-40 to -86°C
Fridge Storage Volume (L)	568L nett
Product Dimensions (mm) (wxdxh)	885x995x1980
Interior Dimensions (mm) (wxdxh)	595x720x1310
Packing Dimensions (mm) (wxdxh)	950x1115x2030
Net/Gross Weight	286/342

Technical data	
Compressor Type	Fixed Frequency
Cooling Type	Direct Cooling
Defrost Type	Manual
Climate Class	N
Rated Voltage/Frequency (V/Hz)	220V/50Hz
Rated Power (w)	2210
Rated Current (A)	12
Decibel Rating (dBA)	54
Refrigerant/Amount (g)	R601a/70g, R290/7g, R1150/18g (each separate refrigerant circuit)

Control	
Sensor Qty	3
Sensor Type	NTC
Controller	Microprocessor
Display	LED

Product Performance	
Temperature Accuracy	0.1°C
Temperature uniformity/°C	≤5°C

Alarms	
	Sound, light, power failure, sensor failure,
Yes	environment temperature, door ajar, high
	temperature, low temperature, remote.

Accessories	
USB	Υ
Door Heating	Υ
Lock	Υ
Backup Battery	Υ
Backup Battery Endurance	52h
Shelves/Drawers Qty	3 shelves
Cable Port	Υ
Castors/type	4 + 2 Levelling Feet