Vacc-Safe

ULT Freezer

VS-86L838 838 Litre

Suitable for storing **vaccines**, **medicines** and **laboratory products and samples** between -40°C and -86°C in pharmacies, hospitals, medical clinics and laboratories.





VIP Plus Insulation.

Provides up to 30% more storage capacity than a conventionally insulated freezer.



Increased Product Lifespan.

Dissipates heat 20% more effectively to improve life expectancy of core parts.



Multi-layer Silicone Sealing Structure.

Provides a tight seal between inner and outer door for better insulation.



Heated Pressure Equalization Port.

Allows users to re-open the main door quickly.



Improved Cooling Performance.

Patented Smart-Inverter technology significantly reduces the amount of energy consumed whilst maintaining superior temperature stability.



Built-In Backup Battery



Security



Single LED Display



USB Data



Lockable

Vacc-Safe

ULT Freezer VS-86L838 838 Litre

Product structure data	
Temperature Range	-40 to -86°C
Fridge Storage Volume (L)	838L nett
Product Dimensions (mm) (wxdxh)	1175x995x1980
Interior Dimensions (mm) (wxdxh)	885x720x1310
Packing Dimensions (mm) (wxdxh)	1240x1115x2030
Net/Gross Weight	332/401

Technical data	
Compressor Type	Inverter
Cooling Type	Direct Cooling
Defrost Type	Manual
Climate Class	N
Rated Voltage/Frequency (V/Hz)	220V/50Hz
Rated Power (w)	2030
Rated Current (A)	9.5
Decibel Rating (dBA)	51
Refrigerant/Amount (g)	R601a/90g, R290/9g, R1150/23g (each separate refrigerant circuit)

Control		
Sensor Qty	3	
Sensor Type	NTC	
Controller	Microprocessor	
Display	LED	

Product Performance	
Temperature Accuracy	0.1°C
Temperature uniformity/°C	≤5°C

Alarms	
Yes	Sound, light, power failure, sensor failure, environment temperature, door ajar, high temperature, low temperature, remote.

Accessories	
USB	Υ
Door Heating	Υ
Lock	Υ
Backup Battery	Υ
Backup Battery Endurance	52h
Shelves/Drawers Qty	3 shelves
Cable Port	Υ
Castors/type	4 + 2 Levelling Feet



1175 mm