

# Vacc-Safe

## Essential Refrigerator VS350 350 Litre

Suitable for storing **vaccines, medicines** and **laboratory products** between 2°C and 8°C in pharmacies, hospitals, medical clinics and laboratories.



### Strong Cooling Airflow.

Downward airflow works as an air curtain to block the external hot air entering the refrigerator when a door is opened.



### Increased Product Lifespan.

Dissipates heat 20% more effectively to improve life expectancy of core parts.



### Heated Doors Stop Condensation Fog.

Accuracy within 0.1°C giving the utmost confidence that goods are stored with precision.



### High Precision Temperature Control.

Accuracy within 0.1°C giving the utmost confidence that goods are stored with precision.



### QCPP Approved.

Quality tested and approved by the Pharmacy Guild and Quality Care Pharmacy Program.



Security



LED Display



DC Turbo Fan



Built-In Air Duct



Self Closing Door

**Vacc-Safe** Australia's leading **vaccine** and **medical** cold storage **manufacturer**

1/13-15 Kevlar Cl Braeside, VIC 3195

(03) 8338 1205

query@vaccsafe.com.au

[vaccsafe.com.au](http://vaccsafe.com.au)



### Product structure data

Temperature Range	2–8°C
Fridge Storage Volume (L)	316L nett
Product Dimensions (mm) (wxdxh)	595x603x1920
Interior Dimensions (mm) (wxdxh)	500x464x1343
Packing Dimensions (mm) (wxdxh)	660x665x2000
Net/Gross Weight	68/76

### Technical data

Compressor Type	Fixed Frequency
Cooling Type	Forced air cooling
Defrost Type	No frost
Climate Class	N
Rated Voltage/Frequency (V/Hz)	220V/50Hz
Rated Power (w)	190
Rated Current (A)	1.5
Decibel Rating (dBA)	52
Refrigerant/Amount (g)	R600/ 36g
Energy Consumption (kwh/24h)	2.5

### Control

Temp HI / LOW Reset	Y
Sensor Qty	4
Sensor Type	NTC
Controller	Microprocessor
Display	LED

### Product Performance

Temperature Accuracy	0.1°C
Temperature uniformity/°C	≤2°C

### Alarms

Yes	Sound, light, sensor failure, environment temperature, door ajar, high temperature, low temperature.
-----	--

### Accessories

USB	Y
Anti-Condensation Door	Electrical heating
Lock	Y
Backup Battery	N
Backup Battery Endurance	N/A
Shelves/ Drawers Qty	5 Shelves
Cable Port	Y
Castors/type	4 (Omni directional)
Warranty	24 Months