

Vacc-Safe

Premium Refrigerator VS50 50 Litre

Suitable for storing **vaccines, medicines** and **laboratory products** between 2°C and 8°C in pharmacies, hospitals, medical clinics and laboratories.



Strong Cooling Airflow.

Downward airflow works as an air curtain to block the external hot air entering the refrigerator when a door is opened.



Increased Product Lifespan.

Dissipates heat 20% more effectively to improve life expectancy of core parts.




Heated Doors Stop Condensation Fog.

Accuracy within 0.1°C giving the utmost confidence that goods are stored with precision.



High Precision Temperature Control.

Accuracy within 0.1°C giving the utmost confidence that goods are stored with precision.



Improved Cooling Performance.

Patented Smart-Inverter technology significantly reduces the amount of energy consumed whilst maintaining superior temperature stability.



Built-In Backup
Battery



Security



LED Display



DC Turbo Fan



Built-In Air Duct



Self Closing Door



USB Data



Vacc-Safe Australia's leading **vaccine** and **medical** cold storage **manufacturer**

1/13-15 Kevlar Cl Braeside, VIC 3195

(03) 8338 1205

query@vaccsafe.com.au

vaccsafe.com.au



Product structure data

Temperature Range	2–8°C
Fridge Storage Volume (L)	50L Gross
Product Dimensions (mm) (wxdxh)	450x459x570
Interior Dimensions (mm) (wxdxh)	380x300x410
Packing Dimensions (mm) (wxdxh)	520x530x640
Net/Gross Weight	23/26

Technical data

Compressor Type	Fixed Frequency
Cooling Type	Forced air cooling
Defrost Type	No frost
Climate Class	N
Rated Voltage/Frequency (V/Hz)	220V/50Hz
Rated Power (w)	100
Rated Current (A)	0.75
Decibel Rating (dBA)	45
Refrigerant/Amount (g)	R600/ 18g
Energy Consumption (kwh/24h)	0.65

Control

Temp HI / LOW Reset	Y
Sensor Qty	2
Sensor Type	NTC
Controller	Microprocessor
Display	LED

Product Performance

Temperature Accuracy	0.1°C
Temperature uniformity/°C	±3°C

Alarms

Yes	Sound, light, power failure, sensor failure, environment temperature, door ajar, high temperature, low temperature.
-----	---

Accessories

USB	Y
Anti-Condensation Door	Low-E Glass
Lock	Y
Backup Battery	Y
Backup Battery Endurance	15h
Shelves/ Drawers Qty	1 shelf/1 drawer
Cable Port	Y
Castors/type	N
Warranty	24 months

