

Vacc-Safe

Vaccine Refrigerator

VS150 150 Litre

Suitable for storing **vaccines, medicines** and **laboratory products** between 2°C and 8°C in pharmacies, hospitals, medical clinics and laboratories.



Inbuilt USB Data Logger.

Data can be traced and exported from the refrigerator itself to give the most accurate data readings.



Increased Product Lifespan.

Dissipates heat 20% more effectively to improve life expectancy of core parts.



High Precision Temperature Control.

Accuracy within 0.1°C giving the utmost confidence that goods are stored with precision.



QCPP Approved.

Quality tested and approved by the Pharmacy Guild and Quality Care Pharmacy Program.



**Built-In Controller
Backup Battery**



Security



LCD Display



DC Turbo Fan



USB Data



Built-In Air Duct

Vacc-Safe Australia's leading **vaccine** and **medical** cold storage **manufacturer**

1/13-15 Kevlar Cl Braeside, VIC 3195

(03) 8338 1205

query@vaccsafe.com.au

vaccsafe.com.au



Product structure data

Temperature Range	2–8°C
Fridge Storage Volume (L)	150L nett
Product Dimensions (mm) (wxdxh)	595x615x810
Interior Dimensions (mm) (wxdxh)	505x467x620
Packing Dimensions (mm) (wxdxh)	665x675x860
Net/Gross Weight	42/48

Technical data

Compressor Type	Fixed Frequency
Cooling Type	Forced air cooling
Defrost Type	No frost
Climate Class	N
Rated Voltage/Frequency (V/Hz)	220V/50Hz
Rated Power (w)	100
Rated Current (A)	1.0
Decibel Rating (dBA)	45
Energy Consumption kWh(24h)	0.78
Refrigerant/Amount (g)	R600

Control

Temp HI / LOW Reset	N
Sensor Qty	3
Sensor Type	NTC
Controller	Microprocessor
Display	LCD

Product Performance

Temperature Accuracy	0.1°C
Temperature uniformity/°C	±2°C

Alarms

Yes	Sound, light, sensor failure, door ajar, high temperature, low temperature.
-----	---

Accessories

USB	Y
Anti-Condensation Door	Low E glass with heating
Lock	Y
Controller Backup Battery	Y/20h
RS485	Y
Shelves/ Drawers Qty	2 Shelves
Cable Port	Y
Castors/type	N/2 leveling feet
Warranty	24 months