

Vacc-Safe


Combined Fridge/Freezer VSC-25L350

Vacc-Safe medical Refrigerators and Freezers can be used in hospitals, epidemic prevention stations, universities and scientific research institutes.



Top Cooling.

Strong cooling airflow from the top to the bottom, works as an air curtain to block the external hot air from entering the refrigerator when the door is opened.




Increased Product Lifespan.

Dissipates heat 20% more effectively to improve life expectancy of core parts.



Multi-layer Silicone Sealing Structure.

Provides a tight seal between inner and outer door for better insulation.



Improved Cooling Performance.

Patented Smart-Inverter technology significantly reduces the amount of energy consumed whilst maintaining superior temperature stability.



**Built-In Controller
Backup Battery**



Security



LED Display



USB Data



Lockable

Vacc-Safe Australia's leading **vaccine** and **medical** cold storage **manufacturer**

1/13-15 Kevlar CI Braeside, VIC 3195

(03) 8338 1205

query@vaccsafe.com.au

vaccsafe.com.au



Product structure data

Temperature Range	Fridge 2°C to 8°C Freezer -10°C to -25°C
Fridge Storage Volume (L)	Fridge 206L Freezer 144L
Product Dimensions (mm) (wxdxh)	695x655x1920
Interior Dimensions (mm) (wxdxh)	Fridge 600x505x690 Freezer 540x480x560
Packing Dimensions (mm) (wxdxh)	755x715x2025
Net/Gross Weight	109x121

Technical data

Compressor Type	Fixed Frequency
Cooling Type	Fridge, Forced air cooling Freezer, Direct Cooling
Defrost Type	Fridge, Auto defrost Freezer, Manual defrost
Climate Class	N
Rated Voltage/Frequency (V/Hz)	220V/50Hz
Rated Power (w)	160
Rated Current (A)	1.8
Energy Consumption (kwh/24h)	1.2
Decibel Rating (dBA)	45
Refrigerant/Amount (g)	mixed

Control

Sensor Qty	4
Sensor Type	NTC
Controller	Microprocessor
Display	LED

Product Performance

Controller Temperature Accuracy	0.1°C
Temperature uniformity/°C	≤1.5°C

Alarms

Yes	Sound, light, power failure, sensor failure, environment temperature, door ajar, high temperature, low temperature, remote.
-----	---

Accessories

USB	Y
Lock	Y
Backup Battery	Y
Backup Battery Endurance	15h
Shelves/ Drawers Qty	Fridge 3/ Freezer 3
Cable Port	Y
Castors/type	2 + 2 Levelling Feet